

Standex Product Catalogue 2016



PRODUCT GUIDE



The Art of Refinishing.

Standex products are for professional use only and distributed to the Trade through a nationwide network of Appointed Distributors.

Our Customer Services team will be pleased to supply you with the name and address of your nearest Distributor, or visit our Website at www.standex.co.uk.

For all technical datasheets referenced in this catalogue, please visit www.standex.co.uk/tds.

To fulfil the Color for Life warranty conditions, certain Standox products must be used, as part of a product system according to the technical data sheets. These products are indicated by the following symbol:



Single usage of one product is not a product system in the sense of Color for Life warranty conditions. The conditions of the Color for Life warranty are on the Repair Certificate. For more information, please see our website.

For a full range of non-paint items available then please visit www.standoshop.co.uk.



Standex UK,
Unit 1, Quadrant Park, Mundells,
Welwyn Garden City, Herts AL7 1FS
Tel: 01707 518000
Fax: 01707 331424
Email: contact-uk@axaltacs.com
Web: www.standex.co.uk

An Axalta Coating Systems Brand

The Repair Process

Standex is one of the world's leading manufacturers of automotive refinishing paints, offering innovative and environmentally compatible product systems for modern bodyshops. The quality of a refinish starts with the use of the right preparation materials. Standox offers a wide range of primers, fillers and polyester products for any area of application. No matter which substrate has to be coated or which application technique is used – Standox has a practical and efficient solution for any application. Standox products meet the environmental regulations of the EU and feature great user friendliness and efficiency.

A wide variety of different material is used on modern vehicles. Correct identification of substrates is essential before work begins. A superb finish is only possible once the substrate is identified and the right preparation process is used.



Cleaning (before the vehicle is worked on)

Start with washing the vehicle thoroughly using a cleaning detergent and wash off with plenty of clean water. Dry the vehicle thoroughly and then clean the repair area using Standox Silicon Remover. Apply product to the area and wipe dry with a lint free cloth.

Sanding (preparatory work)

Sand the damaged area to bare metal.

Stopper application

Remove sanding dust and clean the damaged area using Standox Silicon Remover. Apply product to the area and wipe dry with a lint free cloth. Apply the Standox Stopper.

Sanding

When the Stopper has dried, sand the damaged area as required. Apply additional stopper if necessary.

Cleaning

Thoroughly remove all sanding dust and clean the damaged area using Standox Silicon Remover. Apply product to the area and wipe dry with a lint free cloth. Mask the area around the damaged part.

Primer Filler application

Areas which are sanded to bare metal must be treated with an anti corrosion primer (Standex Etching Adhesion Primer U3100). Apply a Standox 2K Filler as per Technical Data Sheet.

Sanding

After applying a guide coat to the primed area, dry sand.

Once the sanding process is complete, sand the rest of the repair area with an ultrafine sanding pad or ultrafine abrasive.

Cleaning

Thoroughly remove all sanding dust and clean the damaged area using Standox Silicon Remover. Apply product to the area and wipe dry with a lint free cloth.

Masking

Mask as necessary.

Cleaning prior to basecoat application

Clean the whole area using Standox Silicon Remover, apply the product to the area and wipe dry with a lint free cloth. Clean the entire repair area using Standox Precleaner, apply the product to the area and wipe dry with a lint free cloth. Wipe the area using a tack cloth.

Basecoat application

Apply Standohyd Plus Basecoat as per Technical Data Sheet.

Clearcoat application

After the recommended flash-off time, apply a Standox 2K Clearcoat as per Technical Data Sheets.

Polishing

After a suitable drying time, minor defects such as dust inclusions or sagging can be removed.

A perfect result

Proper preparation is the best way to obtain a brilliant finish.

A stack of nine horizontal ribbons, each a different color, arranged vertically. The ribbons are slightly curved and overlap. From top to bottom, the colors are: yellow, orange, brown, green, grey, light blue, blue, and purple. Each ribbon has a white border and contains black text.

Cleaners

Stoppers

Primers/Fillers

Basecoats

Clearcoats

Hardeners

Thinners

Ancillaries



Silicone Remover

- Pre-treatment agent
- Substrate pre-treatment of sanded paintwork and filled substrates

Pack Size: 5 litre

GMC Code: 4024669770278 (Toluene free) & 4024669867862

TDS Number: 992 & 991



Standox Precleaner

- Waterborne cleaning agent
- Mild odour
- Reduced solvent emissions
- For preliminary cleaning of sanded finishes and primed surfaces
- Use as a preclean before Standohyd application

Pack Size: 5 litre

GMC Code: 4024669801323

TDS Number: 803



Standoflex Plastic Cleaner Antistatic

- Solvent blend cleaner with antistatic effect
- For preliminary cleaning of plastic substrates

Pack Size: 1 litre

GMC Code: 4024669825350

TDS Number: 998



Spray Filler U1100



- Spray stopper
- Easy to sand
- Pore-free surface
- Can be used as a fine stopper
- Mix with 5% Standex PE Hardener U1110
- Film thickness up to 1000 micron

Pack Size: 1 litre

GMC Code: 4024669781717

TDS Number: 231



PE Rapid Stopper U1080



- Multi-purpose PE stopper coarse or fine
- Good infrared drying & vertical stability
- Easy to sand
- Excellent adhesion on all substrates
- Mix with 2-3% Standex Hardener paste U1120
- Air dry 15-20 min / 18-22°C
- Dry sand P80 - P240

Pack Size: 3 kg

GMC Code: 4024669860856

TDS Number: 240



PE Soft Stopper U1090



- Multi-purpose PE stopper coarse or fine
- Particularly suitable for infrared drying
- Good vertical stability
- Easy to sand
- Excellent adhesion on all substrates
- Mix with 2-3% Standex Hardener paste U1120
- Air dry 15-20 min / 18-22°C

Pack Size: 2 & 3 kg

GMC Code: 4024669869484 & 4024669874136

TDS Number: 212



PE Fine Stopper U1070



- Easy to spread
- Pore-free, fine surface
- Easy to sand, very good feather edging
- Suitable for steel, UP:GF and aluminium
- Mix with 2-3% Standox Hardener paste U1120
- Do not apply to galvanised substrates
- Air dry 20-30 min / 18-22°C
- Dry sand P180 - P240

Pack Size: 1 kg
GMC Code: 4024669865066
TDS Number: 230

CBR PUTTY 2109



- Good adhesion to steel, aluminum and zinc
- Easy handling
- Good adhesion to automotive parts
- Perfect machining properties after curing
- Cures at room temperature
- Very low shrinkage after full cure

Pack Size: 200 ml
GMC Code: D15335223



Standoflex Pore Filler U3080



- 1K Pore Filler for micropores in plastic surfaces
- Apply by wiping

Pack Size: 250 grams
GMC Code: 4024669750089
TDS Number: 740



Standoflex Plastic Stopper Black U1030



- Plastic Stopper for PC exterior plastic parts providing very good flexibility
- Good adhesion direct to plastic
- Can be used in conjunction with Standoflex Plastic Primer U3060 to achieve excellent adhesion properties
- Easy to spread and gives a pore-free and fine surface
- Very easy to sand
- Available in black colour shade and comes in a kit with a dedicated white hardener

Pack Size: 1.14 kg

GMC Code: 4024669826401

TDS Number: 741

1K Adhesion Primer U3030 Red Brown



- 1K acid primer, Chromate-free
- Certified for welding
- Easy to apply
- Outstanding corrosion protection
- Add 50% thinner
- 1 - 2 spray passes
- Overcoat with Standox Filler after 15-20 min / 18-22°C flash off

Pack Size: 1 litre
GMC Code: 4024669862126
TDS Number: 411

1K Primer Filler U3010



- 1K acid primer, Chromate-free
- Corrosion protection
- Certified for welding
- 1 spray coat
- Overcoat with Standox VOC Filler after 10-15 min / 18-22°C flash off

Available in Light Grey and Dark Grey

Pack Size: LG; 1 & 3.5 litre DG; 3.5 litre
GMC Code: LG; 4024669848724, 4024669848991 DG; 4024669849295
TDS Number: 413

SprayMax 1K Primer Filler U3010



- 1K acid primer, Chromate-free
- Corrosion protection
- Certificate for welding
- 1 spray pass
- Overcoat with Standox Filler after 10-15 min / 18-22°C flash off

Available in Light Grey, Dark Grey, White and Black

Pack Size: 400 ml
GMC Code: LG; 4024669756609 DG; 4024669756791 W;
4024669757767 B; 4024669757507
TDS Number: 1204

Standoflex Plastic Primer U3060



- 1K Primer for use in a 3-stage plastic painting system
- Easy to apply
- Adheres to all exterior plastic car parts
- Ready to spray
- 1 spray pass
- Overcoat wet-on-wet with plasticised Standox Filler
- Flash off 10 min / 18-22°C

Pack Size: 400 ml & 1 litre

GMC Code: 4024669849967 & 4024669812701

TDS Number: 720



Standoflex 2K Plastic Primer Surfacer U3200



- Easy application & handling
- Adheres to all exterior plastic car parts
- Wet-on-Wet working process or can be used as a sanding filler
- Mixing ratio 1:1 with Standoflex 2K Plastic Hardener U3210
- Ready to spray after addition of hardener
- Two-coat system
- Potlife 8-10 h / 18-22°C

Pack Size: 1 litre

GMC Code: 4024669825510

TDS Number: 750



VOC Transparent Adhesion Sealer U7520



- VOC compliant
- Optimised for use under Standox VOC compliant basecoat
- Isolator for critical substrates
- Especially economical for overall respray
- Can be used as a transparent filler
- Can be used for structuring of plastic parts together with Standox Structure Additives
- Mix 3:1 with all Standox VOC Hardeners

Pack Size: 1 litre

GMC Code: 4024669780727

TDS Number: 1601

Etching Adhesion Primer U3100



- 2K acid primer
- Excellent adhesion, Chromate-free
- For use in a 3-stage systems
- Outstanding corrosion protection
- Mix 1:1 with Standox Etching Adhesion Activator U3110
- Potlife 4-5 days / 18-22°C
- 2 spray passes = 8 micron

Pack Size: 1 litre & 250 ml SprayMax version
GMC Code: 4024669780116 & 4024669756876
TDS Number: 312



EP Primer Surfacer U7200



- Epoxy-based universal primer surfacer
- Chromate-free
- Good isolating properties & infrared drying
- Primer for Standox Spray Filler on zinc
- Good weather-resistant properties
- Mix 3:1 with Standox EP Hardener U7210
- 2 - 3 spray coats

Pack Size: 1 litre
GMC Code: 4024669850154
TDS Number: 932



VOC System Filler U7540



- VOC compliant
- Good vertical stability & filling properties
- Easy to sand with good isolating properties
- Excellent tension & Chromate-free
- Mix 7:1 with Standox VOC Hardeners

Available in White, Grey & Black

Pack Size: 3.5 litre
GMC Code: W; 4024669780567 G; 4024669780819 B; 4024669780796
TDS Number: 539



VOC Nonstop Primer Surfacer U7580



- VOC compliant
- Direct to metal or plastic application
- Excellent anti-corrosion and adhesion properties
- Very good application properties
- One visit application for wet-on-wet process
- Short flash-off time

Available in Light Grey & Black

Pack Size: 3.5 litre

GMC Code: LG; 4024669780758 & B; 4024669780772

TDS Number: 1602



VOC Pro Filler U7530



- Excellent air drying
- VOC compliant & highly productive sanding filler
- Good vertical stability & filling properties
- Chromate-free
- Good isolating properties
- Mix 7:1 with Standox VOC Hardeners

Available in Grey, White & Black

Pack Size: 3.5 litre

GMC Code: G; 4024669780710 W; 4024669780789 B; 4024669780734

TDS Number: 543

Easy Filler U7010



- 2K Sanding Filler
- Good vertical stability
- Good filling properties
- Easy to sand
- Chromate-free
- Mix 6:1 with Standox VOC Easy Hardener

Pack Size: 3.5 litre

GMC Code: 4024669845693

TDS Number: 547

SprayMax 1K Spotfill Primer U3020



- Isolation Sealer for small through-sanded areas to bare metal on edges and corners
- Fast flash off time
- 1 Visit Application
- Can be over-coated with Standohyd Plus Basecoat
- Available in SprayMax aerosol
- Slight denibbing with soft pad ultra-fine possible

Pack Size: 400 ml

GMC Code: 4024669862133

TDS Number: 1223



Standohyd Plus Basecoat



- Easy to blend in
- Good opacity
- High coverage
- Outstanding colour accuracy
- Contains less than 10% organic solvent
- Solid, metallic, pearl colours
- Thin with Standohyd Demineralised Water
- 1 working spray pass

TDS Number: 801

Standohyd Plus Mixing Enamels



4024669556704	Mix 009	Metallic Additive	500ml
4024669520163	Mix 306	Gold	500ml
4024669553079	Mix 307	Midnight Black	1lt
4024669553109	Mix 310	Effect White	500ml
4024669860153	Mix 311	Satin Silver	1lt
4024669553123	Mix 312	Silver Dollar Fine	500ml
4024669860061	Mix 313	Moon Silver	1lt
4024669553475	Mix 347	Cranberry Red	500ml
4024669552539	Mix 353	Brilliant Orange	500ml
4024669521139	Mix 355	Violet	500ml
4024669551105	Mix 356	Scarlet	500ml
4024669555974	Mix 357	Ocean Blue	1lt
4024669553581	Mix 358	Velvet Blue	500ml
4024669552102	Mix 359	Blue	1lt
4024669551129	Mix 361	Rubin Red	1lt
4024669860085	Mix 362	Jet Black	1lt
4024669553635	Mix 363	Black	500ml
4024669552409	Mix 364	Black Toner	500ml
4024669550504	Mix 365	Red	500ml
4024669553666	Mix 366	Purple	500ml
4024669550450	Mix 367	Red Oxide	500ml
4024669520835	Mix 368	Ochre Toner	500ml
4024669552768	Mix 369	Violet Toner	500ml
4024669860092	Mix 370	White	1lt
4024669860115	Mix 372	Special Black	1lt
4024669553734	Mix 373	Emerald	500ml
4024669550245	Mix 374	Ochre	500ml
4024669554762	Mix 376	Brilliant Red	500ml
4024669521726	Mix 377	Dark Yellow	500ml
4024669556902	Mix 378	Sun Yellow	500ml
4024669521801	Mix 379	Orange	500ml
4024669520910	Mix 380	Yellow	500ml
4024669552492	Mix 382	Copper	500ml
4024669553833	Mix 383	Maroon	500ml
4024669521054	Mix 384	Wine Red Toner	500ml
4024669521566	Mix 385	Lemon Yellow	500ml
4024669553864	Mix 386	Brilliant Maroon	500ml
4024669553888	Mix 388	Azure Blue	500ml
4024669553895	Mix 389	Green	500ml

Basecoats

4024669553338	Mix 390	Silver	1lt
4024669553178	Mix 393	Coarse Silver	1lt
4024669860139	Mix 394	Fine Silver	1lt
4024669553956	Mix 395	Extra Fine Silver	500ml
4024669553987	Mix 398	Brilliant Silver	500ml
4024669521993	Mix 399	Transparent	500ml

Standohyd Plus Pearl Mixing Enamels

4024669502893	Mix 289	Indigo Fine Pearl	250ml
4024669502909	Mix 290	Carribbean Blue Pearl	250ml
4024669553765	Mix 301	White	1lt
4024669553024	Mix 302	Yellow	500ml
4024669554069	Mix 303	Blue	1lt
4024669554007	Mix 304	Red Pearl	500ml
4024669553055	Mix 305	Titian Red	500ml
4024669554502	Mix 321	Amethyst	500ml
4024669521481	Mix 323	Moss Green	500ml
4024669553246	Mix 324	Light Green	500ml
4024669554403	Mix 325	Aquamarine	500ml
4024669520248	Mix 328	Brown	500ml
4024669553604	Mix 329	White	500ml
4024669520323	Mix 331	Red	500ml
4024669520408	Mix 336	Ermine	500ml
4024669520590	Mix 339	Sapphire Blue	500ml
4024669520675	Mix 341	Almadin	500ml

Standohyd Plus Xirallic Mixing Enamel

4024669522105	Mix 326	Satin White	500ml
4024669522020	Mix 327	Satin Red	500ml
4024669520682	Mix 343	Satin Gold	500ml
4024669520699	Mix 344	Satin Copper	500ml
4024669520705	Mix 345	Satin Blue	500ml
4024669520712	Mix 346	Satin Green	500ml

Standohyd Plus Special Enamels

4024669503425	Mix 142	Sunset Red	250ml
4024669502435	Mix 143	Magic Cyan	250ml
4024669502442	Mix 144	Midnight Blue	250ml
4024669502459	Mix 145	Paradise Green	250ml
4024669502466	Mix 146	Mystic Gold	250ml
4024669502473	Mix 147	Rainbow Silver	250ml
4024669551488	Mix 348	Velvet Rose	250ml
4024669551495	Mix 349	Mystic Violet	250ml
4024669551501	Mix 350	Sunrise Orange	250ml

Standohyd Plus Ready Mix

4024669606713		Jet Black	1ltr
---------------	--	-----------	------

Exclusive Line Red Rocket



- Limited edition special colour
- Pearlescent effect paint
- Standohyd Basecoat system
- Ready Mix
- Thin with Standohyd Demineralised Water

Pack Size: 1 litre
GMC Code: 4024669268805
TDS Number: 676

2K Fluorescent Red



- High quality 2K fluorescent paint
- Extremely luminous
- Meets FRG regulations
- Mix 7:1 with all Standox VOC Hardeners
- 10-20 % Standox 2K Thinner
- 6-8 spray passes min. 100 micron

Pack Size: 1 litre
GMC Code: 4024669870817
TDS Number: 580



Standocryl VOC Platinum Clear K9570

- Special VOC Clear with reflow effect for improved abrasion resistance
- Durable high gloss for 2-stage finishes
- Extremely high mechanical and chemical resistance
- Mix 3:1 with Standox VOC Hardener 30-40 or Standox VOC Hardener 20-25

Pack Size: 1 litre
GMC Code: 4024669841336
TDS Number: 586



Standocryl VOC 2K Clear K9550

- High quality VOC clear for partial and total respray
- Good polishability
- Outstanding gloss and flow
- User friendly application properties with two spray passes
- 3:1 VOC System with Standox VOC Hardeners

Pack Size: 5 litre
GMC Code: 4024669841343
TDS Number: 1503



Standocryl VOC Express Clear K9530

- High quality VOC clear for partial and total respray
- Very fast drying
- Good polishability
- Flexible in application and drying conditions
- 3:1 VOC System
- 1 working spray pass
- Force drying 15-30 min / 50-60°C panel temperature

Pack Size: 5 litre
GMC Code: 4024669841374
TDS Number: 1505



Standocryl 2K HS Clear K9520



- High quality 2K Clear for panel repair and overall re-sprays
- High solid product
- Excellent vertical stability
- Material and time savings by reducing the number of spray passes
- Mix 3:1 with Standox VOC Hardeners
- 1.5 Spray passes

Pack Size: 5 litre
GMC Code: 4024669824971
TDS Number: 564

Standocryl VOC Easy Clear K9510



- VOC Clear for 2-stage finishes
- Ready to spray after addition of hardener
- Good application
- Mix 2:1 with Standox VOC Easy Hardeners
- 1.5 Spray passes

Pack Size: 5 litre
GMC Code: 4024669860023
TDS Number: 1502

Standocryl VOC Xtreme Clear K9580



- Energy saving, super fast curing Clearcoat
- 15 min at 40°C or Air drying < 1 h at 20°C
- Excellent gloss and flow
- Exceptional one visit application

Pack Size: 1 litre and 5 litre
GMC Code: 4024669841442 & 4024669841459
TDS Number: 1508

VOC Hardener 10 - 20



- Fast hardener for accelerated drying
- Application temp: 10-20 °C
- Suggested repair sizes:
 - Local spot / Micro repair
 - Single small panels - not horizontal panels

Pack Size: 1 litre

GMC Code: 4024669793123

Painting Table Number: T2C & T3_1C



VOC Hardener 25 - 30



- Medium hardener for general application
- Application temp: 20-25 °C & 25-30 °C
- Suggested repair sizes:
 - Multiple panels - small to medium repair area
 - Medium to large repair area

Pack Size: 1 litre

GMC Code: 4024669793062

Painting Table Number: T2C & T3_1C



VOC Hardener 30 - 40



- Slow hardener for general application
- Application temp: 25-30 °C & 30-40 °C
- Suggested repair sizes:
 - Multiple panels - medium to large repair area
- Use slower hardener as repair size and/or temperature increase

Pack Size: 1 litre

GMC Code: 4024669793024

Painting Table Number: T2C & T3_1C



Etching Adhesion Activator U3110



- Mix 1:1 with Etching Adhesion Primer U3100

Pack Size: 1 litre
GMC Code: 4024669780123
TDS Number: 312



EP Hardener U7210



- Mix with EP Primer Surfacer U7200

Pack Size: 1 litre
GMC Code: 4024669850147
TDS Number: 931



Standoflex 2K Plastic Hardener U3210



- Use with Standoflex 2K Plastic Primer Surfacer U3200

Pack Size: 1 litre
GMC Code: 4024669825602
TDS Number: 750



PE Hardener U1110



- For use only with Spray Filler U1100
- This allows the Spray Filler to dry in 2 hours

Pack Size: 50 ml
GMC Code: 4024669829181
TDS Number: 231



PE Hardener Paste U1120 Red



- For use with all Standox Stoppers mixed between 2 - 3%

Pack Size: 90 grams
GMC Code: 4024669853728
TDS Number: 211, 212 & 240



BPO Hardener Paste Red



- For use with all Standox Stoppers mixed between 2 - 3%

Pack Size: 50 grams
GMC Code: 1250089283

Hardener VOC Easy 10-20



- For use with VOC Easy Clear K9510 mixed 2:1

Pack Size: 1 litre

GMC Code: 4024669862249

Painting Table Number: T3_1E

Hardener VOC Easy 20-30



- For use with VOC Easy Clear K9510 mixed 2:1

Pack Size: 1 & 2.5 litre

GMC Code: 4024669862188 & 4024669862232

Painting Table Number: T3_1E

Hardener VOC Easy 30-40



- For use with VOC Easy Clear K9510 mixed 2:1

Pack Size: 1 litre

GMC Code: 4024669862218

Painting Table Number: T3_1E

Hardener Xtreme



- For use with VOC Xtreme Clear K9580 mixed 2:1

Pack Size: 1 litre
GMC Code: 4024669793154
TDS: 1508

Hardener Xtreme Fast



- For use with VOC Xtreme Clear K9580 mixed 2:1

Pack Size: 1 litre
GMC Code: 4024669793147
TDS: 1508

Thinner VOC 15-30



- Used to adjust viscosity of Standox Clearcoats and Primers
- For use in ambient temperatures of 20 °C to 30 °C
- Can be used for single panel repairs

Pack Size: 1 & 5 litre

GMC Code: 4024669780017 & 4024669780888

Painting Table Number: T3_2C



Thinner VOC 30-40



- Used to adjust viscosity where temperatures exceed 30 °C
- Will aid the flow on larger areas
- Should also be used as part of the 2K Special Matt system

Pack Size: 1 litre

GMC Code: 4024669781397

Painting Table Number: T3_2C



Smart Blend Plus



- Thinner for blend-in of Standocryl VOC Clears
- Force drying possible
- Air dry overnight / 18-22 °C

Pack Size: 400 ml (aerosol) & 1 litre

GMC Code: D12828247 & 4024669780093

TDS Number: 1206 & 944





Thinner Easy 15-30

- Used to adjust the viscosity of Easy Filler U7010 and VOC Easy Clear K9510 between ambient temperatures of 20 °C to 30 °C

Pack Size: 1 litre
GMC Code: 4024669862065
Painting Table Number: T3_2C



Thinner VOC Express

- For spot & small panel repairs the Thinner VOC Express is particularly good for accelerating the drying time and improving the hardness when used in Standox clearcoats.

Pack Size: 1 litre
GMC Code: 4024669793413
TDS Number: 1505



Demineralised Water



- To be used with Standohyd Plus Basecoat – thin with 10%

Pack Size: 5 litre
 GMC Code: 4024669801880
 TDS Number: 801



VOC 2K Additive



- Used in conjunction with VOC 2K Clearcoat K9550
- Add 5% Standocryl VOC 2K Additive to adjust spray viscosity & improve the properties of the clearcoat.

Available in normal and slow
 Pack Size: 1 litre
 GMC Code: normal; 4024669841367 & slow; 4024669841466
 TDS Number: 1503



Standohyd Plus Special Additive



- Activates Standohyd Plus Basecoat mixed colour to vastly improve 3-stage finish repairs
- Ground colour is activated with 5% of the Standohyd Special Additive to give a hard surface for subsequent coats of the final effect colour.

Pack Size: 500 ml
 GMC Code: 4024669520019
 Painting System Number: S9_5 & S9_6



Special Matt



- An additive for clearcoat matting
- Will provide a silky matt finish or matt finish
- Application of the matted paint in 2 spray passes
- A uniform matt result after drying
- For use on metal and plastic substrates

Pack Size: 1 litre
GMC Code: 4024669862058
Painting System Number: S14
Painting Table Number: T8_6



Standohyd Plus Color Blend



- For blending-in Standohyd Basecoat
- Easy handling
- Ready to spray or mix 1:1 with Standohyd Basecoat

Pack Size: 1 litre
GMC Code: 4024669800456
TDS Number: 806



Clearcoat Additives



- Additive for tinting of clears
- Add Standox Clearcoat Additive to the Clearcoat according to colour being used.
- Available in the following colours:

KA670 Magenta	4024669865400
KA671 Red	4024669865417
KA672 Maroon	4024669865424
KA673 Light Red	4024669865431
KA674 Transparent Red	4024669865448
KA675 Blue	4024669865455
KA676 Brilliant Red	4024669865462

Pack Size: 100 ml
TDS Number: 1504



2K Plasticiser



- Universal plasticiser for all VOC clearcoat systems
- Suitable for Standox Filler
- For plastic finishes
- High long-term elasticity
- For all car plastic panels
- Add 1.5% of plasticiser to clearcoats and fillers used on medium and hard plastics

Pack Size: 1 litre
GMC Code: 4024669840407
TDS Number: 590



Standohyd Plus Transformer



- Convenient multi-coat application
- Very easy to blend in
- Easy defect rectification
- Smooth surface
- Solid, metallic, pearl colours
- 2.5 coat process

Pack Size: 2.5 litre
GMC Code: 4024669559965

VOC Plastic Additive U7590



- For use with Standox VOC Nonstop Primer Surfacer U7580

Pack Size: 1 litre
GMC Code: 4024669780772
TDS: 1602

16.30 Coagulant



- A dedicated material for separating pigment residue from water
- Allows for the safe recycling of any remaining liquid
- Coagulated paint can be filtered out and removed as chemical waste

Pack Size: 850 grams
GMC Code: D12627755

Sontara Polishing Cloth



- An extremely soft cloth for delicate and challenging polishing tasks
- Manual polishing
- Final treatment of external surfaces
- Interior cleaning

Pack Size: 275 cloths per roll
Cloth Size: Roll: 365 x 400 mm
GMC Code: D11257537

Sontara Tack Cloth



- A new generation of tack cloth which leaves no chemical residue on the surface or users' hands
- Reduces the risk of smears or streaks
- Removal of dust and fibres before the application of primers and fillers
- Removal of superfine particles before the application of basecoat
- Cleaning of plastic parts

Pack Size: 1 bag of 12 cloths
Cloth Size: 381 x 432 mm
GMC Code: Folded: D14900724

Sontara Degreasing Cloth



- Extra heavy-duty non-woven cloth
- For use on all types of surface degreasing before the application of paints or coatings
- Can be used for general surface preparation with water, alcohol or solvent based cleaners and the cleaning of painting accessories
- Available folded or on a roll

Pack Size: 200 folded cloths per carton/ 200 cloths per roll

Cloth Size: Folded: 325 x 420 mm Roll: 325 x 390 mm

GMC Code: Folded: D11257548 Roll: D11257504



Standex UK

Unit 1, Quadrant Park, Mundells, Welwyn Garden City, Herts AL7 1FS

Tel: 01707 518000 Fax: 01707 331424

Email: contact-uk@axaltacs.com

An Axalta Coating Systems Brand